STAC5-Q-N220

AC Advanced Microstep Drive w/ Q Programming

1pc. - 660.00 50pc. - 495.00



Product Features

- Programmable, microstepping digital step motor driver in compact package
- Advanced anti-resonance algorithm
- Torque ripple smoothing
- Microstepping to 51,200 steps/rev
- Operates from 220 VAC
- Provides motor current up to 2.55 A/phase (peak of sine) with idle current reduction
- Fast 10/100 Ethernet for programming and communications
- 744 lines of stored Q program capability
- Math calculations using analog and digital parameters
- Supports all STAC5-S control modes as well
- UDP & TCP support
- 12 digital inputs, 6 digital outputs, all optically isolated
- 1 analog input, +/-10 volt range



Description

The STAC5-Q-N220 stepper drive employs sophisticated current control designed for optimal smoothness over a wide speed range. Anti-resonance, torque ripple smoothing, and microstepping work together to bring step motor performance to a new high. To complement the drive Applied Motion offers a specially matched set of low-loss NEMA 23 and 34 frame motors (see Related and Recommended Products below), all specifically designed with high voltage operation in mind. Power to the drive comes from single-phase 220 VAC, and the drive can output up to 2.55 A/phase (peak-of-sine) to the step motor. Protection features like over-voltage, over-temperature, and over-current prevent damage while running in adverse conditions.

The STAC5-Q-N220 can operate in all of the same control modes as a STAC5-S drive (pulse & direction, velocity, streaming commands), plus it has the ability to run stand-alone Q programs stored in non-volatile memory. Q programs are created using the *Q Programmer™* software, which provides multi-tasking, math functions, conditional processing, data register manipulation, and more features in a robust yet simple text-based programming language. Initial setup of the drive, including selecting the control mode, setting up the motor, and configuring other drive parameters is done using the *ST Configurator™* software.


For connecting to external devices such as limit switches, proximity or photoelectric sensors, PLC I/O, lamps, and other devices, the drive comes with 12 digital inputs, 6 digital outputs, and 1 analog input. The drive also features an Ethernet port for configuration and communications. The Ethernet port is fast 10/100 Mbit, and the drive supports both TCP and UDP communication protocols.


This step motor drive is UL Recognized (File No. E332730), CE approved, and RoHS compliant.

Specifications

Model Number:	STAC5-Q-N220
Part Number:	5000-201
Supply Voltage:	94-265 VAC
Supply Voltage Type:	AC
Control Modes:	Streaming Commands Analog Positioning Encoder Following Q Programming
Output Current:	0.5-2.55 A/phase
Communication Ports:	Ethernet
Encoder Feedback:	No
Step Resolution:	Full
	Half Microstepping Microstep Emulation
Idle Current Reduction:	0-90%
Setup Method:	Software setup
Digital Inputs:	12
Digital Outputs:	6
Analog Inputs:	1
Dimensions:	5.5 x 4.5 x 2.0 inches
Weight:	22.4 oz
Operating Temperature Range:	0-70 °C
Ambient Temperature Range:	0-40 °C
Ambient Humidity:	90% max, non-condensing
Status LEDs:	1 red, 1 green
Circuit Protection:	Short circuit Over-voltage Under-voltage Over-temp

Torque Curves





Software

Software: SCL Utility

ST Configurator™

Sample Code: C_sharp_UDP_example.zip

WB6_UDP_example.zip

WB6_TCP_example.zip


Downloads

Manuals:	STAC5 Hardware Manual 920-0026C.pdf STAC5 QuickSetupGuide 920-0040 .pdf Host Command Reference Rev I.pdf eSCL_Comm_Reference.pdf				
Datasheet:	http://s3.amazonaws.com/applied-motion-pdf/STAC5-Q-N220.pdf				
Family Datasheet:	STAC5_Datasheet_925-0003.pdf				
2D Drawing:	☐ STAC5.dxf ☐ STAC5-1.pdf ☐ STAC5_simple_3D.pdf				
3D Drawing:	STAC5.igs				
Speed-Torque Curves:	STAC5_speed-torque.pdf				
Agency Approvals:	STAC5_SVAC3_CE_DOC.PDF				
Application Notes:	APPN0020-Maple-Systems-with-Ethernet-Drive.zip APPN0019 Analog-positioning-using-Q-program.zip APPN0016_Simple-25-pin-mating-connections.pdf				

Pricing

	STAC5-Q-N220 Part No. 5000-201
1pc.	\$660.00
25pc.	\$567.60
50pc.	\$495.00
100рс.	Contact us for 100+ piece pricing.

2D Drawings



Products in the Series STAC5 Stepper Drives

Model Number	Supply Voltage	Control Modes \$	Output Current	Communication Ports	Encoder Feedback	1pc./50pc. 💠
STAC5-IP- E120	94-135 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming, EtherNet/IP	0.5-5.0 A/Phase	Ethernet, EtherNet/IP	Yes	\$710.00 / \$532.50
STAC5-IP- E220	94-265 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming, EtherNet/IP	0.5-2.55 A/Phase	Ethernet, EtherNet/IP	Yes	\$710.00 / \$532.50
STAC5-IP- N120	94-135 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming, EtherNet/IP	0.5-5.0 A/Phase	Ethernet, EtherNet/IP	No	\$659.00 / \$494.25
STAC5-IP- N220	94-265 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming, EtherNet/IP	0.5-2.55 A/Phase	Ethernet, EtherNet/IP	No	\$659.00 / \$494.25
STAC5-Q- E120	94-135 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming	0.5-5.0 A/Phase	Ethernet	Yes	\$726.00 / \$544.50
STAC5-Q- E220	94-265 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming	0.5-2.55 A/Phase	Ethernet	Yes	\$726.00 / \$544.50
STAC5-Q- N120	94-135 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming	0.5-5.0 A/Phase	Ethernet	No	\$660.00 / \$495.00
STAC5-Q- N220	94-265 VAC	Streaming Commands, Analog Positioning, Encoder Following, Q Programming	0.5-2.55 A/Phase	Ethernet	No	\$660.00 / \$495.00
STAC5-S- E120	94-135 VAC	Step & Direction, Velocity (Oscillator), Streaming Commands	0.5-5.0 A/Phase	Ethernet	Yes	\$471.00 / \$353.25
STAC5-S- E220	94-265 VAC	Step & Direction, Velocity (Oscillator), Streaming Commands	0.5-2.55 A/Phase	Ethernet	Yes	\$471.00 / \$353.25
STAC5-S- N120	94-135 VAC	Step & Direction, Velocity (Oscillator), Streaming Commands	0.5-5.0 A/Phase	Ethernet	No	\$405.00 / \$303.75
STAC5-S- N220	94-265 VAC	Step & Direction, Velocity (Oscillator), Streaming Commands	0.5-2.55 A/Phase	Ethernet	No	\$405.00 / \$303.75